

Materijal za zatrpavanje

Zaštitni sloj

SikaProof® P-1200 membrana

SikaProof® ljepilo

Vanjski konstruktivni zid

Zaptivanje konstruktivnog spoja
(minimalno SikaSwell® A)

> 50 mm

> 100 mm

Preklopna površina SikaProof® A+ membrane
mora biti tretirana otvorenim plamenom
prije lijepljenja

Temeljna konstrukcija

SikaProof® A+ membrana

Podloga/podložni beton

Tlo

SikaProof® A+ - PRELAZ SA TEMELJNE PLOČE NA ZID

Sa SikaProof® P-1201 lijepljenim sistemom za naknadnu ugradnju

Sika BH d.o.o.

Džemala Bijedića 299

71000 Sarajevo

Bosna i Hercegovina

Tel: +38733 788 390

www.sika.ba

DRAWING MUST ALWAYS BE REVIEWED BY A DESIGN SPECIALIST AND IF NECESSARY MODIFIED TO ENSURE SUITABILITY FOR THE SPECIFIC APPLICATION

The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein and is based on laboratory tests which do not replace practical tests. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

BUILDING TRUST

