

Sarnaplast®-2235 ili Sikaflex®-11 FC zaptivna masa
sa potpornim užetom i odgovarajućim prajmerom

Sarnabar® šina sa Sarnafast® vijcima i
Sarnafil® T užetom za zavarivanje

Zavarivanje vrućim zrakom

Sarnafil® TG 66 membrana,
slobodno položena

Opločnici, min. balast 12 kg/m²
za svakih 10 mm termoizolacije

Zaštitni sloj (po potrebi)

Sikatherm® / Sarnatherm®,
termoizolacija

Sarnavap® parna brana

Podlošci za opločnike sa križnim distancerima

≥ 150 mm

Odgovarajući S-Felt nivelirajući sloj
(po potrebi)

Limeni opšav

Sarnafil® TG 66 membrana,
preklop

Sarnavap® ljepljiva traka

**SARNAFIL® TPO - PROHODNI KROV SA OPLOČNICIMA
NA BETONSKOJ PODLOZI SA TERMOIZOLACIJOM**
SF TPO - 040.04.01 - Svjetlarnik sa zaptivenom membranom

DRAWING MUST ALWAYS BE REVIEWED BY A DESIGN SPECIALIST AND IF NECESSARY MODIFIED TO ENSURE SUITABILITY FOR THE SPECIFIC APPLICATION

The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein and is based on laboratory tests which do not replace practical tests. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika BH d.o.o.

Džemala Bijedića 299

71000 Sarajevo

Bosna i Hercegovina

Tel: +38733 788 390

www.sika.ba

BUILDING TRUST

